



Elgiloy Specialty Metals – Wire Products

Hastelloy® B-3® alloy

UNS N10675
W. Nr 2.4600

Applicable Specifications

Wire & Bar | ASTM B335

Description: Hastelloy® B-3® alloy is a nickel-molybdenum alloy with increased structural and thermal stability compared to that of Hastelloy® B-2®. It has excellent resistance to pitting, corrosion, and stress corrosion cracking in high-purity acid environments. It has excellent resistance to hydrochloric acid at all concentrations and temperatures. The alloy can withstand most concentrations of sulfuric, acetic, formic, and phosphoric acids, as well as other nonoxidizing media. Hastelloy® B-3® can be cold worked to increase strength with limited effects on general corrosion resistance but is recommended to be re-annealed for optimum stress corrosion cracking resistance.

Applications include: Reaction vessels, Welding wire, Fittings, Rings, Springs

Industries supplied include: Chemical Processing

Nominal Composition

C	Mn	Si	S	P	Ni	Cr	Mo	Co
0.01 max	3.0 max	0.10 max	0.03 max	0.030 max	65.0 min	1.0 - 3.0	27.0 - 32.0	3.0 max
Nb (Cb)	V	Al	Cu	Ta	Ti	W	Zr	Fe
0.20 max	0.20 max	0.50 max	0.20 max	0.20 max	0.20 max	3.0 max	0.10 max	1.0 - 3.0

Physical Properties

	At 70°F	At 20°C
Density	0.333 lb/in ³	9.22 g/cm ³
Modulus of Elasticity (E)	31.4 x 10 ³ ksi	216 GPa
Coefficient of Expansion	6.5 µin/in-°F (70-1200°F)	11.8 µm/m-°C (25-600°C)
Electrical Resistivity	53.8 µohm-in	136.6 µohm-cm
Thermal Conductivity	78 Btu-in/ft ² -hr-°F	11.2 W/m-°C

Typical Mechanical Properties

Condition	Heat Treatment	Tensile Strength	Suggested Operating Conditions
Annealed	1950°F (1066°C)	120-150 ksi (827-1035 MPa)	-320°F to 1200°F (-200°C to 650°C)
Spring Temper	None	200 ksi min (1379 MPa)	Up to 750°F (400°C)

Hastelloy® B-3® and B-2® are registered trademarks of Haynes International, Inc.

Limitation of Liability and Disclaimer of Warranty:

- The content in these data sheets is provided primarily by third-party melting mills and is provided for reference only. It is not intended for engineering or design.
- Applications may be discussed, however, Elgiloy Specialty Metals, a Division of Combined Metals of Chicago L.L.C., does not recommend or endorse any material for any particular end use or application.
- The data included in this data sheet are typical values and may vary.
- Elgiloy Specialty Metals, a Division of Combined Metals of Chicago L.L.C., makes no representations or warranties, express or implied, as to the accuracy, completeness, condition, suitability, performance, fitness for a particular purpose, or merchantability of any information contained in any data sheet.
- In no event will Elgiloy Specialty Metals, a Division of Combined Metals of Chicago L.L.C., be liable for any damages whatsoever arising from the use of the information included in the data sheets.

For further information:

Email: wireinquiries@elgiloy.com

Phone: 1-847-695-1900

Elgiloy Specialty Metals – Wire Products

356 North Cross Street

Sycamore, IL 60178 USA

www.elgiloy.com

Rev Date: 6/17/2020