

Elgiloy Specialty Metals – Strip Products

Alloy 2507 Stainless Steel

UNS S32750 W. Nr 1.4410

Applicable Specifications

Strip and Foil

ASTM A240, NACE MR0175/ISO 15156

Description: Alloy 2507 is a super-duplex (austenitic/ferritic) stainless steel designed for applications which require exceptional strength and corrosion resistance surpassing that of 304 and 316 stainless steels. The alloy has excellent resistance to stress corrosion cracking as well as pitting, crevice, and erosion corrosion. Alloy 2507 also has high thermal conductivity, a low coefficient of thermal expansion, and good weldability.

Applications include: Desalination equipment, Saltwater handling, Flue gas desulfurization, Food processing equipment, Heat exchangers, Pulp mill bleach systems, and Oil distillation

Industries supplied include: Chemical Processing, Food Processing, Oil & Gas, and Power Generation

Nominal Composition										
	С	Si	Mn	Р	S	Cr	Ni	Мо	N	Cu
min	-	-	-	-	-	24.0	6.0	3.0	0.24	-
max	0.030	0.80	1.20	0.035	0.020	26.0	8.0	5.0	0.32	0.50

	At 70°F				At 20°C					
Physical Properties										
max	0.030	0.80	1.20	0.035	0.020	26.0	8.0	5.0	0.32	0.50
111111						24.0	0.0	5.0	0.24	

 Density
 0.280 lb/in³
 7.8 g/cm³

 Modulus of Elasticity (E)
 29.0 x 10³ ksi
 200 GPa

 Modulus of Rigidity (G)
 10.9 x 10³ ksi
 75 GPa

 Coefficient of Expansion
 7.2 μin/in-°F (70-212°F)
 12.96 μm/m-°C (20-100°C)

 Electrical Resistivity
 32.7 μohm-in
 83.0 μohm-cm

Typical Mechanical Properties

Thermal Conductivity

Condition	Heat Treatment	Tensile Strength	Suggested Operating Conditions			
Annealed	1920-2100°F (1050-1150°C)	1150-145 ksi (800-1000 MPa)	-58°F to 572°F (-50°C to 300°C)			

Elgiloy Specialty Metals - Strip Products 1565 Fleetwood Dr. Elgin, IL 60123 USA

Phone: 1-888-843-2350 www.elgiloy.com

118 Btu-in/ft2-hr-°F

REV 2024 04 02

17.0 W/m-°C

LIMITATION OF LIABILITY AND DISCLAIMER OF WARRANTY:

The content in these data sheets is provided primarily by third-party melting mills and is provided for reference only. It is not intended for engineering or design.

Applications may be discussed, however, Elgiloy Specialty Metals does not recommend or endorse any material for any particular end use or application.

The data included in this data sheet are typical values and may vary.

Elgiloy Specialty Metals makes no representations or warranties, express or implied, as to the accuracy, completeness, condition, suitability, performance, fitness for a particular purpose, or merchantability of any information contained in any data sheet.

In no event will Elgiloy Specialty Metals be liable for any damages whatsoever arising from the use of the information included in the data sheets.